



# **User's Manual**

COMMUNITY

GLOBAL


For your safety and effective use of this product, please read the instructions carefully.


# Using the device

# 1.1. The basic diagram of product



GLOBAL





#### **Product overview**

Nanofibre Technology with electret effect can improve filtration efficiency of particles PM 2.5 to 99%. Purely Mask for air purification has excellent deep cleaning effect, at the same time, by circulation, active against humidity, exhaust gases.

Comprehensive solution for difficult breathing, shortness of breath, etc.

#### 1.2. Parts of the device



- 1. S-unit
- 2. Internal clamp
- 3. Breathing Valve
- 4. The system of filters
- 5. Cover
- 6. External clamp
- 7. Input air
- 8. Indicator
- 9. Air module
- 10. Cover of the filter
- 11. Collapsible tool for filter cover

# 1.3. On / switching modes



- 1. Switch button is at the top, as shown.
- 2. Switching on the device requires continued pressing in the course of 1 second. The mask is equipped with three speeds, which you adjust by pressing a button. To switch off, continuously press button for more than 1.5 seconds.
- 3. When you switch on the device, mode will remain the way it was prior to shutting down.



- 1. The first time you need to make full discharge and charge the device.
- 2. In normal operation of the device, blue LED shines brightly. If blue indicator flashing, the device requires recharging.
- 3. Open the slide of USB port, plug a charger cable to charge the device.
- 4. During charging, red LED shines brightly. When red LED is off, that means full charge.
- 5. After charge, please close the rubber cap at USB-connector.



Micro USB charging jack

## 2.1 Replacement and disassembly of Air filtration plate















By hands or tools push the filter cover, turn it counterclockwise, a filter lid automatically pops; Remove a filter and you will see blue Air filtering plate;

Remove an old filtering plate;

Take a new filtering plate and insert it properly;

By hands or tools take a filter cover and slowly rotate clockwise.

## 2.2 Disassembly Air module, replace a mask filter











Firmly squeeze an air-cleaning module and rotate clockwise;

Turn to the end, to be able to lift Air-module;

Firmly squeeze an inner and outer terminals;

Open an inner clamp;

Remove a filter system to be replaced.

### 2.3 How to use spare cover and filter cover

















Turn to the end, to be able to lift Air-module;

Take a back cover;

Put the filter cover and rotate it until it clicks;

Nanofibre filtration plate with effect of electret can be used separately.

## Cases in which the guarantee is not provided

- 1. Unauthorized repair, misuse; strikes, negligence, wrong use, damage, alteration, misuse parts, torn label or marking;
- 2. Excess warranty;
- 3. Force majeure, which resulted in damage to the product;
- 4. Damage, that do not meet «fault list of products»;
- 5. User created all sorts of problems, installing new systems and components, that are not included in the «List of faults.»

#### **List of Faults**

- 1. The lack of production;
- 2. Can not turn on the device;
- 3. The indicator does not work;
- 4. Device buttons do not work;
- 5. Other manufacturing errors.

# Name and content of harmful substances in products

Parts name				Harmful substances		
	Pb	Hg	Cd	Cr 6+	PBE	PBDE
Body	0	0	CO 0 240	0	0	CO O WUNIT
PCB	Х	<b>~</b> 0	0	0	0 /	0
Wire	0	0	0	0	0	0
Accessories	0	0	0	0	OMMUNITY	OUBAL

# 2.4 How to wear a respirator:

- 1. Pre-stretch straps before you put it. Make sure the clip on the nose directed upwards.
- 2. Press the respirator so that he closed his chin and nose; fasten the strap on the ear or use the S-node to connect the straps to the mask adhere to the face.
- 3. Press nose clip by fingers so that it lies flat tightly to the bridge.
- 4. Switch on a mask to clear the air.

#### 3. Product paremeters

Product Name: Purely air clean mask;

Product type: HZSN001; Rated voltage: DC 5 V; Rated power: 0.4 V; Weight: 50.5 grams;

Product Size: 75x37x13 mm;

Applicable standards: Q / HZSN001-2016;

Shelf life: 3 years;

Material: Polyester fiber polypropylene plastics;

#### 3.1 Features

Lithium polymer battery 550 mA/h;

Hours: 4-8 pm;

Ultra-quiet fan with a duration of 30,000 hours;

Note: respiratory filter plate should be changed once a week.

#### Purely air clean mask

WECHAT account: iPurely;

Ltd. Hangzhou Suynenh technology;

Producer: Ltd. Dongguan Tian Jie;

Address: Dongguan, Chang'an town, district Tou Yuen Street, Hung E

number 4.

Official website: www.suineng.com.cn